







FBA-G1 1 kg FE-36™ **Ozone Friendly Automatic Fire Suppression Units**
FBA-G2 2 kg FE-36™



-  FE-36™ Clean agent (Halon replacement)
-  Zero ozone depletion
-  Manufacturer's 5 year warranty
-  Manufactured in UK
-  Suitable for B & C class fires
-  Safe for use on electrical equipment
-  Powder coated, steel wire bracket

Used to protect machinery/plant and where there is a risk of fire such as in boat/vehicle engine compartments. The unit required is determined by the gross volume of that compartment. Only one unit should be installed in any one compartment and should provide the total protection required for that compartment.

FBA-G1 provides protection for a maximum enclosed volume of 1.7m³
FBA-G2 provides protection for a maximum enclosed volume of 3.4m³

Model	FBA-G1	FBA-G2
Capacity	1 kg	2 kg
Total Weight	2.05 kg	3.5 kg
Total Height	340 mm	385 mm
Total Width (including bracket)	125 mm	135 mm
Working Temp.	-20° to +80°C	-20° to +80°C
Discharge Time / Temperature	8 secs @ 79°C ± 5°C	8 secs @ 79°C ± 5°C
Maximum Volume Protected	1.7 m ³	3.4m ³
Operating Pressure	12 bar @ 20°C	12 bar @ 20°C
Minimum Burst Pressure	55 bar	55 bar
Packing Specification		
Qty Per Carton		
Carton Dimensions		
Carton Volume		
Carton Weight		
Qty Carton per Pallet		
Pallet Dimensions		
Pallet Volume		
Pallet Gross Weight		